

KS-7215 Series

www.posiflex.com

| Specification                  | KS-7215   |
|--------------------------------|---|
| Processor                      | Intel Pine View D525 1.8 GHz / 1 M Cache CPU (Dual Core)  |
| System Memory                  | DDR3 800 MHz, SO-DIMM socket x 1, max 4 GB, default 1 GB  |
| Storage Device                 | 2.5" SATA HDD or SSD Kit (Optional) or CF Kit (Optional)  |
| Power Supply                   | 12V DC power adaptor, 60W<br>(Optional 80W when equipping with 2nd LCD LM-8015/8025/8035/8045/TM-8045) (Black Only)   |
| Audio                          | 2W speaker  |
| OS support                     | Win 7 / Win XP Pro / POSReady 7 / POSReady 2009 / Linux   |
| Color                          | Black / White   |
| Display                        |   |
| LCD                            | 15" TFT LCD, 1024 x 768 resolution  |
| Touch Function                 | Resistive, 5-wire, USB Interface / IR touch, USB Interface<br>Bezel-free, Resistive touch, USB Interface<br>Bezel-free, PC touch, USB Interface   |
| Brightness Control             | By digital push botton  |
| Tilt Adjustment                | From 15° to 70°   |
| Connectivity                   |   |
| LAN Port                       | 10 / 100 / 1000 Mb  |
| Parallel Port                  | Optional  |
| Serial Port                    | DB9 x 2, RJ-45 x 2 (Optional RJ-45 to DB9 cable),<br>with 5V / 12V support on COM1 / COM2 / COM3 / COM4   |
| UPS Port                       | Yes,battery (Optional)  |
| Standard USB Port              | 6   |
| Proprietary USB Port           | 1 for side mount options  |
| Powered USB                    | 1 X 24V via 5.5th gen base (Upgrade to 150W power adaptor when equipped with Powered USB) (Black Only)  |
| VGA Port                       | D-SUB 15 pins, with 12V power for Posiflex LCD monitor  |
| CR Port                        | 1, control 2 CR   |
| Physical Dimension             |   |
| Dimension<br>(W x D x H in mm) | 378 X 304 X 364   |
| Weight (N. W. in kg)           | 7.7   |
| Environment                    |   |
| Operation Condition            | 0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)   |
| Storage Condition              | (-20°C) - 70°C, 10%RH - 90%RH   |
| Options                        |   |
| PD-306 / PD-306U               | 2 x 20 LCD, default 200 mm pole (Black Only)  |
| PD-309 / PD-309U               | 2 x 20 LCD, default 200 mm pole (Black Only)  |
| PD-310 / PD-310U               | 2 x 20 LCD, rear top mount (Black / White)  |
| PD-2602 / PD-2602U             | 2 x 20 VFD, default 200mm pole (Black Only)   |
| PD-2604 / PD-2604U             | 2 x 20 VFD, rear top mount (Black / White)  |
| PD-2605 / PD-2605U             | 2 x 20 VFD, default 200 mm pole (Black Only)  |
| PD-76X2                        | 240 x 64 dot graphics LCD,<br>200 mm pole (Black Only)  |
| SSD                            | 8 GB minimum  |
| CF Card                        | Type I card   |
| MSR                            | See security device   |
| Security Device (SD)           | <b>SD-460/SD-460Z:</b> 3 tracks MSR (JIS-II optional) and/or Finger Print Sensor (SD-460 (Black / White))<br><b>SD-660W:</b> 3 tracks MSR (JIS-II optional) and/or iButton (SD-660 (Black Only))<br><b>SD-860W:</b> 3 tracks MSR (JIS-II optional) and/or RFID and/or WiFi (SD-860 (Black / White)) |
| UPS Battery                    | 2300 mAh / 12V  |
| RAID Function                  | Support RAID 1 (Disk mirroring)   |
| 2nd LCD Display                | 15" LM-8015B/8025/8035/8045/TM-8045<br>12" LM-6101B/LM-2312<br>10" LM-2310 (Black Only)   |
| 2nd HDD                        | 2.5" SATA HDD   |
| KP-300W                        | 36 Key plus lock keypad and/or MSR and/or smart card reader   |
| Certifications                 | <div>FCCESGSUKASSGSRoHSGreenMarkWindows Embedded PartnerSAPORACLE</div>   |

Design and Manufacturing In Taiwan by Posiflex Technology Inc.

\*\* The product information and specifications are subject to change without prior notice.

2012 KS72Q3C1



Posiflex Technology, Inc.  
Headquarters  
No.6, Wuquan Rd., Wugu Dist., New Taipei City  
248, Taiwan (R.O.C.)  
Tel: +886 2 2299-1599 Fax: +886 2 2299-1819  
sales@posiflex.com.tw www.posiflex.com

Authorized Distributor / Reseller

KS-7215 Series

Advanced Innovative  
FanFree POS Terminal

Elegant Bezel-Free Design



**POSIFLEX**  
Your Success is Our Vision



## Key Features

- ▶ Resistive, IR, Bezel-free Resistive, or Bezel-free PC touch screen for 15" LCD
- ▶ 15" LCD 1024 x 768 resolution
- ▶ Spill-resistant design to prevent careless spill and provide easy cleaning for a wide range of applications
- ▶ Equipped with Intel Pine View Dual Core D525 1.8 GHz CPU and DDR3 memory
- ▶ Fan-free design boasting quiet and anti-dust features
- ▶ Patent aluminum die casting design for efficient cooling
- ▶ RAID 1 support to backup important data (Optional)
- ▶ UPS (Embedded on board developed by Posiflex) support to avoid sudden power loss
- ▶ Patent finger lever "Gear Lock" to adjust the LCD tilt angle from 15° to 70°
- ▶ Push-open cover to protect power switch from accidental shutdown
- ▶ Bottom cable guide design and cover for safety and neat outlook
- ▶ User-friendly mechanism for system upgrade and easy maintenance
- ▶ Shiny diamond black or white front bezel for stunning look (Optional)
- ▶ Generation 6 super slim base stand (Optional)



with customer pole display



Adjustable LCD



with MSR and finger print scanner



Posiflex unveils the fanfree KS-7215 series as an advanced innovative POS terminal.

The KS-7215 series catches people's attention by its streamlined and patent aluminum die casting design, bezel-free touch screen, RAID 1 backup, as well as UPS functions. The bezel-free appearance sparks the shop decoration. Built-in UPS function is embedded on main board developed by Posiflex for power backup. Spill-resistant and anti-dust features allow it to operate silently even in a harsh environment.

Besides, the KS-7215 series supports Intel Pine View Dual Core 1.8 GHz CPU with 15" touch screen in a small footprint. It also supports versatile peripheral options such as MSR, customer pole display, programmable keypad, and a wide range of connectivity to meet numerous applications.

*The KS-7215 series presents innovative features and high performance for retailers who concern about data protection.*

